



SIMOLI

AUTOMATED DILUTION WATER SYSTEM FOR PALM OIL MILL



www.simolindo.com minfo@simolindo.com





Disadvantages :


- 1. Difficult to adjust a constant hot water flow rate.
- 2. Fluctuated volume of Hot Water Tank give different flow rate to the output.
- 3. Need more attention and supervision to stabilize the flow rate.
- 4. Consumed more water, and unstable solution concentration.
- 5. More water in solution, more centrifuge machine on operation. More sludge produce at Sludge Tank.

PROPOSED AUTOMATED WATER DILUTION SYSTEM FOR PALM OIL MILL

Working Procedure :

- 1. Signal taken from press unit (how many presses are in operating)
- 2. By knowing numbers of presses in operation, also known how much dilution water needed.
- 3. lot flowmeter read the existing flowrate in.
- 4. The microcontroller will adjust the lot Valve to open or close to meet the needed for water dilution via signal from press unit.
- Incase any repair at IoT line, the water flow can use by pass system using analog flow meter for temporary

Automated Dilution Water System



Advantages :

- 1. Supply of hot water can be adjusted automatically precise as required.
- 2. Microcontroller will organize the flow corresponding to the running Mill capacity.
- 3. At the beginning mill processing, standard figures for water flow rate can be set for every single press machine.
- 4. The figures/system can be monitored via computers and Smartphone
- 5. Save water consumed as well as energy produced.

Water Dilution Calculation for POM

Press capacity 15 tph per unit DCO approximately 60 – 70 % to FFB Dilution water approximately 30 % to DCO

Calculation water dilution base on Press Unit running :

- 1 Press : 2.70 3.15 m3/hr
- 2 Press : 5.40 6.30 m3/hr
- 3 Press : 8.10 9.45 m3/hr
- 4 Press : 10.80 12.60 m3/hr

THANK YOU